

# WindFoil 130 wind barrier

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 40-2018	
1. Product type:	WindFoil 130
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	For use under roof covering of discontinuous roofs of buildings, for use in walls of buildings. The products must be installed in accordance with manufacturer's instructions.
4. Name and contact address of the manufacturer	<b>DAFA A/S</b> Holmstrupgaardvej 12, DK-8220 Brabrand
5. Authorized representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	No 1434
8. Notified body (ETA)	N/A

**9. Declared performance** Harmonized technical specification EN 13859-1:2010 "Flexible products for water tightness. Part 1: Underlays for discontinuous roofing"

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Length	EN 13859-1		25 (-0)
Width			3,05 (-0,5/+1,5%)
Mass per unit area			130 ± 6%
Resistance to water penetration		Class	W1
Water vapor transmission, Sd		m	0,02 (-0,01/+0,03)
Dimensional stability (MD&CD)		%	<2
Reaction to fire		Class	E
Flexibility at low temperature		°C	≥-40
Tensile strength along MD		N/50mm	320 ± 30%
Tensile strength across CD		N/50mm	220 ± 30%
Elongation along MD		%	55 ± 30%
Elongation across CD		%	55 ± 30%
Tear resistance along MD		N	160 ± 20%
Tear resistance across CD		N	225 ± 20%



# WindFoil 130 wind barrier

Declaration of Performance acc. to EU 305/2011


The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Brabrand, 18-01-2018

Jan Thuesen, Supplier Quality Engineer

A handwritten signature in blue ink is written over a horizontal dashed line. The signature is stylized and appears to be 'J. Thuesen'.