

# DAFA roof decking vent



## Warranty.

DAFA offers a function and product warranty for 10 years on all products associated with DAFA AirVent System.

DAFA roof decking vent is part of DAFA AirVent System and can be installed in all standard roof fabrics from outside and in and inside and out.

### Application

DAFA roof decking vent is used to ensure ventilation through roof decking fabrics and can be used with all diffusion-open- and dense roof decking fabrics as well as fixed roof decking.

### Installation

The vent is easily installed in the fabric from the inside. This is a big advantage as it is often complicated to install it subsequently from the outside.

### Advantages

- Effectively ventilates the attic area against moisture and rot
- Quick and easy installation from the outside and in or from inside and out due to "snap-lock"
- Seals tightly when the strip is pulled
- Can be installed in all materials
- Variable dimensions from 0,2 mm to 25 mm
- Installation requires only one person
- 56 cm<sup>2</sup> ventilation area

### Material

DAFA roof decking vents are manufactured in UV-resistant polypropylene/TPE.

### Dimensions

W: 153 mm  
H: 36 mm  
Ø: 100 mm

### Delivery

Delivered in 6 bags of 10 pieces per box (960 pr. pallet)

Read more at [www.dafa-group.com](http://www.dafa-group.com)



Inside-out



Outside-in



### Product information

Type	DAFA no.	EAN no.	DB no.	NOBB no.
Inside-out	620032802	5705636455297	1978192	53566380
Outside-in	620032803	5705636455303	1978193	53566395

# DAFA roof decking vent

## Installation guide

### Outside-in installation



### Inside-out installation

