

DAFA butyl tape

DAFA Butyl tape is a part of DAFA Radon System and is an elastic butyl sealing strip for securing radon barriers.

Application

DAFA butyl tape is an elastic butyl sealing tape for affixing radon barriers

Areas of application

- Construction seal for radon membranes
- Special seals in renovation work
- Metal structures, containers, cold stores

Material

DAFA Butyl tape is an extruded special butyl sealing strip, coated with stretch film.

Installation

DAFA Butyl tape is mounted in a way that the radon barrier overlaps efficiently (100 - 150 mm) and covers the entire surface.

Remove the cover sheet. Press DAFA Butyl tape firmly against the surface.

Installation temperature:

+5 °C to +25 °C.

Attention!

Surfaces must be completely clean, dry and free of grease and dust.

Benefits

- DAFA butyl tape is included in the Nordic Ecolabellings database of construction products that can be used in Swan labelled buildings.
- Adheres tightly to most building materials
- Solvent-free
- Does not dry out, retains elasticity
- Does not rub off on fingers or mounting surfaces
- Very long-lasting durability
- The product does not contain harmful substances



DAFA Butyl tape for special sealing is a very flexible sealing strip.

Technical specifications

Density	1,1 g/cm ³
Temperature resistance	-40 °C to +90 °C
Water absorption	Negligible
Resistance to UV light	Excellent
Basic raw material	Butyl
Color	Black
Adhesion	Good on PE-foil, metal, glass, wood and concrete
Aging resistance	Good

Roll width

20 mm

Length per roll

25 m

Contents per box

10 rolls

DAFA item no.

620032588

EAN no.

5705636454429



Eurofins-certification A+

