

DAFA Flex 600

Declaration of Performance acc. to EU 305/2011

ETA-15/0652

Declaration of Performance no. 35-2015	
1. Product type:	DAFA Flex 600
2. Identification of the product	Lot no. – see label on paper core
3. Intended use or uses of the product	Joint sealing tape based on a pre-compressed flexible impregnated polyurethane foam for sealing around windows and joints in building facades
4. Name and contact address of the manufacturer	DAFA A/S, Holmstrupgaardvej 12, DK-8220 Brabrand
5. Authorised representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 4
7. Notified body (hEN)	N/A
8. Notified body (ETA)	ETA-Danmark A/S

9. Declared performance. Harmonised technical specification ETA-15/0652

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Reaction to fire	EN 13501-1	Class	F
Driving rain resistance	EN 12208	Pa (class 9a)	Tight up to 600
Air permeability of joints	EN 1026	m ³ /h*m ² (daPa) ^{2/3}	a ≤0,029
Resistance to water vapor diffusion	EN ISO 12572		μ=4,1
Temperature resistance			-20 to +80 °C



dafa-group.com

Denmark · Sweden · Germany · China · US · Norway · Poland · Italy



DAFA Flex 600

Declaration of Performance acc. to EU 305/2011

No. TP600-20130522

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Brabrand, 06-11-2015

Jan Thuesen, Supplier Quality Engineer

