

DAFA EzyFold™ Folded Tape



Warranty.

DAFA offers a function and product warranty for 10 years on all products associated with DAFA AirStop System.

DAFA EzyFold folded tape is part of the DAFA AirStop System and is a specialized tape that is pre-folded for sealing both internal and external corners and edges.

Application

The pre-folded, highly adhesive tape is particularly suitable for connecting window and door frames to indoor airtight layers (vapor barriers).

The unique fold of the tape makes installation easy and secure around corners and angles.

Its special folding technique with a split liner makes it particularly well-suited for challenging sealing applications.

The tape can be applied to most building materials (e.g., OSB boards, concrete, chipboard, and steel) as well as directly onto the vapor barrier.

Material

The high-performance adhesive system ensures excellent adhesion values.

The unique acrylic dispersion adhesive maintains high performance even when exposed to moisture and steam, increasing the expected lifespan of the seal—especially for building materials that are subject to expansion and contraction.

Fordele

- Pre-folded in 12/48 mm and 30/30 mm
- Split liner for easy application
- Part of the DAFA AirStop System
- Effectively seals difficult corner joints
- Strong adhesive tape



DAFA EzyFold - 30/30 mm fold

Designed for difficult internal and external corner joints. (Picture 1)

DAFA EzyFold - 12/48 mm fold

Ensures the tape does not extend beyond the plasterboard edge. (Picture 2)

Technical Specifications

Name	Method	Unit	Result
Thickness without liner	DIN EN 1942	mm	0,32 - 0,36
Peel value	DIN EN 1939	N/mm	≥ 25
Installation temperature		°C	Recommended from +5
Tack			Excellent
Temperature resistance		°C	-30 to +120
S _D value		m	approx. 1

Item numbers

Type	Contents per carton	DAFA No.	EAN No.
30/30 mm	7 rolls of 25 m.	620042768	5705636270265
12/48 mm	5 rolls of 25 m.	620042767	5705636270258

