

DAFA Paint & Plaster airtight tape - with split liner

DAFA P&P tape provides airtight sealing on surfaces such as wood, PVC, gypsum board, and brickwork. The split liner makes application easier, and the tape can be plastered and painted over.



Warranty.

DAFA offers a function and product warranty for 10 years on all products associated with DAFA AirVent System.

Application area

DAFA Paint and Plaster Tape is a sealing and bonding tape designed for airtight transitions that can be covered with joint compound or plaster. The tape provides strong adhesion to a wide range of building surfaces, including plywood, chipboard, and flexible vapor barrier membranes. It is used for sealing and covering joints where a durable and airtight connection is required. The product meets the requirements of EnEV / DIN 4108-7 for permanent airtightness in vapor barrier constructions.

Product description

Adheres strongly to non-polar and low-energy surfaces, especially PE film, HDPE, PP, and PE fleece.

The high-quality PP nonwoven prevents adhesive absorption into the substrate, even in warm conditions. It stays flat, resists curling, and accommodates thermal expansion and building movement for a durable, long-lasting seal.

The acrylic-blend adhesive maintains strong performance when exposed to moisture and vapor, helping extend the service life of the seal.

DAFA P&P tape is listed/registered in the database of construction products that can be used/included in Nordic Swan Ecolabelled construction.



DAFA Paint & Plaster Airtight Tape



With split liner.

Technical specifications

Material	PP nonwoven
Adhesive system	Acrylic blend
Liner	Silicone paper, white
Thickness (without coating)	0.55-0.60 mm (DIN EN 1942)
Coating weight	230-250 g/m ² (DIN EN ISO 536)
Adhesive strength	≥ 30 N/25 mm (DIN EN 1939)
S _d -value	9 m
Elongation	≥ 50 N/25 mm; 40 % (DIN EN 14410)
Application temperature	Recommended minimum: +5 °C can be applied from -10 °C
Exposure time	Max. 12 weeks
Temperature resistance	-40 °C to +100 °C
Condensation and water resistance	Excellent
Aging resistance	Excellent

Dimension	Split-liner	Contents per carton	DAFA no.	EAN no.
60 mm x 25 m	30/30 mm	10 rolls	620022979	5705636447773
100 mm x 25 m*	50/50 mm	6 rolls	620026531	5705636422015

Verified EPD

Product	Unit	GWP-total (A1-A3)
DAFA P&P Tape	kg CO ₂ eq./kg	1,07

*Non-stock item. Min. order: 240 rolls



Download the EPD here:
dafa-build.com/en/epd
 or scan the QR code

10/2026

