

DAFA Flex 600™ sealing-tape



Warranty.

DAFA offers a function and product warrant for 10 years.

Application

DAFA Flex 600 sealing tape is used for the external sealing of windows and doors and in various industrial sealing applications.

The sealing tape is weatherproof and permeable and therefore prevents the formation of dry rot and mould in the structure.

When you purchase DAFA sealing tape, you can always be sure that the sealing tape has been tested from a minimum of 600 Pa waterproofing, as we know that **ONLY** this withstands Danish weather conditions.

We supply building site guidelines and encourage you to contact us in the relevant project situation for which you need to select sealing tape.

Warranty

DAFA supplies a 10-year total product warranty.



EMICODE is a trademark-protected seal for product classification for modern, solvent-free and low-emission laying materials and construction products. EMICODE EC1 PLUS (very low emission level) is the strictest emission class.

Advantages

- BG1 approved in accordance with DIN 18542.
- Controlled expansion
- Product support
- The widest range on the market
- Tested and approved at max. seal width
- Highly resistant to mould fungus and microorganisms
- Independently tested (in conjunction with Rosenheim)
- DAFA has more than 40 years of experience with sealing tapes
- Quality assurance, min AB92
- Optimal roll lengths = fewer joints



illmod 600 and DAFA Flex 600 are the only sealing tapes on the market constantly being subject to external unannounced quality control regarding waterproofing (made by the Institute MPA BAU Hannover / Materialprüfanstalt für das Bauwesen Hannover).

Product information	Standard	Classification
Approvals	DIN 18542	BG1
Flammability	DIN 4102	Class F
Temperature resistance		-20 °C to +80 °C
Heat conductivity figures	DIN 52612	$\alpha \leq 0,055 \text{ W/mK}$
Vapour diffusion resistance	EN ISO 12572	$S_d < 0,5 \text{ m}$
Weatherproofing	DIN 18542	Passed
Air permeability	EN 1026	$a < 1,0 \text{ m}^3/[\text{h}\cdot\text{m}(\text{daPa})\text{n}]$
Waterproofing	EN 1027	Min. 600 Pa
Compatibility with other substances	DIN 18542	Passed
Peel value of adhesive	EN 1939	$>6 \text{ N} / 25 \text{ mm}$
Color		Grey or black
Shelf-life		12 months
Storage		Store dry and out of direct sunlight, temperature from +1 °C to +20 °C

