

DAFA Butyl 200 joint sealant

DAFA Butyl 200 joint sealant is part of DAFA Facade Kit series and is a non-hardening joint sealant used for sealing in various constructions.

Description

Butyl 200 is a non-hardening joint sealant used for sealing in a range of structures.

Application

For sealing purposes on a wide range of structures, where the butyl is applied in a "tight fit joint". This means areas where there is a form of mechanical fixing (e.g. between a concrete floor and a floor sill). Used for instance in overlapping joints in moulding for caravans and for sealing joints in roof structures.



Information

- Light grey color
- Good UV resistance
- Good resistance against acids and alkalis
- The surfaces must be kept clean, dry and free of oil and grease
- Can be stored for up to one year (in a dry, cool and frost free environment)
- DAFA Butyl 200 joint sealant is included in the Nordic Ecolabellings database of construction products that can be used in Swan-labelled buildings.



Butyl 200, tube 310 ml.



Butyl 200, bag 600 ml.

Type/contents	Contents per box	DAFA no.	EAN no.
Tube, 310 ml	25 tubes	233400100	5705636098944
Bag, 600 ml	12 bags	620010694	5705636313764

Technical specifications

Material	Non-hardening butyl joint sealant		
Temperature resistance	-40 °C to +80 °C		
Installation temperature	+5 °C to +30 °C		
Storage	1 year. Store in dry, cool and frost-free environment		
Density	1,6 g/cm ³		
Resistance	Good UV-resistance. Good resistance against acids and alkalis		
Color	Light grey		

LCA calculation

Product	Unit	GWP-total (A1-A3)
DAFA Butyl 200	kg CO ₂ eq./m ²	1,09

NEW



Download EPD for DAFA Butyl 200 here:
www.dafa-build.com/en/epd
 or scan the QR code

06/2024

