

# DAFA UniFoil 150µm

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 08/2013 Revision 1	
1. Product type:	UniFoil
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	Flexible sheets for waterproofing - Plastic and rubber vapour control layers EN 13984
4. Name and contact address of the manufacturer	<b>DAFA A/S</b> Holmstrupgårdvej 12, DK-8220 Brabrand
5. Authorised representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	0761-CPD, MPA -Braunschweig
8. Notified body (ETA)	N/A

## 9. Declared performance. Harmonised technical specification EN 13984

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Resistance to water penetration	EN 1928	2 kPa	Pass
Water vapor transmission	EN 1931	-0/+20m	70
Tensile strength longitudinal	EN 12311-2	N/5cm -0/+20%	110
Tensile strength transverse	EN 12311-2	N/5cm -0/+20%	100
Elongation longitudinal	EN 12311-2	%	≥450
Elongation transverse	EN 12311-2	%	≥400
Tear resistance longitudinal	EN 12310-1	N -0/+20%	40
Tear resistance transverse	EN 12310-1	N -0/+20%	40
Durability – aging	EN 1296		Pass
Alkali	EN 1847	2 kPa	Pass
Shear resistance of joints	EN 12317-2		NPD
Resistance to impact	EN 12691		NPD
Length	EN 1848-2	m	-0% / +3%
Width	EN 1848-2	m	±1%
Straightness	EN 1848-2	75 mm / 10 m	pass
Mass per unit area	EN 1849-4	g/m <sup>2</sup> ± 7%	140



# DAFA UniFoil 150µm

Declaration of Performance acc. to EU 305/2011

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Brabrand, 21-08-2018

Jan Thuesen, Supplier Quality Engineer

