

DAFA ProFoil

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 01/2022-R3	
1. Product type:	ProFoil
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	Flexible sheets for waterproofing - Plastic and rubber vapour control layers EN 13984
4. Name and contact address of the manufacturer	DAFA A/S Holmstrupgaardvej 12, DK-8220 Brabrand
5. Authorised representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	1434, 0761
8. Notified body (ETA)	N/A

9. Declared performance Harmonised technical specification EN 13984:2013

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Reaction to fire	EN 13501-1	Class	F
Resistance to water penetration	EN 1928	2 kPa	Pass
Water vapour transmission	EN 1931	m ² sPa/kg	3,1*10 ¹¹ ± 40%
Tensile strength longitudinal	EN 12311-2	N/5cm	≥ 130
Tensile strength transverse	EN 12311-2	N/5cm	≥ 120
Elongation longitudinal	EN 12311-2	%	≥ 400
Elongation transverse	EN 12311-2	%	≥ 450
Tear resistance longitudinal	EN 12310-1	N	≥ 70
Tear resistance transverse	EN 12310-1	N	≥ 70
Durability – aging	EN 1296		Pass
Alkali	EN 13984		Pass
Shear resistance of joints	EN 12317-2		NPD
Resistance to impact	EN 12691		NPD



DAFA ProFoil

Declaration of Performance acc. to EU 305/2011

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Brabrand, 15-09-2022

Jan Thuesen, Quality and Environment Manager

