

DAFA DiFoil

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 31-2015 R1 (03/01/2022)	
1. Product type:	DAFA DiFoil
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	Plastic and rubber vapour control layers – EN 13984, type A
4. Name and contact address of the manufacturer	DAFA A/S Holmstrupgaardvej 12, DK-8220 Brabrand
5. Authorised representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	SGS Intron (1939) and BTTG (0338)
8. Notified body (ETA)	N/A

9. Declared performance Harmonised technical specification EN 13984:2013

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Reaction to fire	EN 13501-1	Class	E
Resistance to water penetration	EN 1928 Methode A	2 kPa	W1
Water vapour transmission	EN 1931	m	1,5 – 2,5
Tensile strength longitudinal	EN 12311-2	N/5cm -0/+20%	≥ 110
Tensile strength transverse	EN 12311-2	N/5cm -0/+20%	≥ 100
Elongation longitudinal	EN 12311-2	%	≥ 85
Elongation transverse	EN 12311-2	%	≥ 90
Tear resistance longitudinal	EN 12310-1	N -0/+20%	≥ 80
Tear resistance transverse	EN 12310-1	N -0/+20%	≥ 80
Resistance to impact	EN 12691		≥ 300
Durability – ageing	EN 1296		Pass
Alkali	EN 13984		Pass
Mass per unit	ISO 536	g/m ²	110



DAFA DiFoil

Declaration of Performance acc. to EU 305/2011


The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Brabrand, 03-01-2022

Jan Thuesen, Quality and Environment Manager

A handwritten signature in blue ink, consisting of stylized, overlapping loops and lines, positioned above a horizontal dashed line.