



# DAFA IsoBatt™

## Warranty.

DAFA offers a function and product warranty for 10 years on all products associated with DAFA AirStop System.

### Application

DAFA IsoBatt is used as a separation layer between the existing construction and the vapor barrier, for example during renovation. DAFA IsoBatt functions as the firm underlayer positioned behind the taped joints in the vapor barrier foil.

### Installation

If the existing underlayer is unsuited for application of a foil, for example if there are spikes from nails, screws or similar objects that may damage the foil, DAFA IsoBatt is to be installed before installing the vapor barrier. The plates are cut with a box cutter and is adjusted to the surrounding constructions for example rafters, collar beams or straps. DAFA IsoBatt should be firmly levelled upon completion.

### Product benefits

- Easy to cut and adjust
- Protects the vapor
- Easy to handle
- Reduces dust nuisances

Properties	Value
Polymer type	Polyethylenefoam
Color	White
Hardness	24 ±15% kg/m <sup>3</sup>
Installation temp.	-60 °C to +60 °C
Thermal conductivity	A= 0,055 W/mK

Information	
Color	White / 1000 x 1000 x 25 mm
Contents per pallet	32 pcs
DAFA item no	620027541
DB nr	1863430
EAN nr	5705636429090



DAFA IsoBatt is a flexible PE-foam separation layer used between the underlying construction and the HiFoil foil during external installation.



DAFA IsoBatt protects the vapor barrier against protruding nails and screws.



DAFA IsoBatt are easy to cut and handle.

