

# RooFoil 230MH

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 33-2015	
1. Product type:	RooFoil 230 MH
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	Flexible sheets for waterproofing - Definitions and characteristics of underlays - Underlays for discontinuous roofing
4. Name and contact address of the manufacturer	<b>DAFA A/S</b> Holmstrupgaardvej 12, DK-8220 Brabrand
5. Authorized representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	TBU (0799): Report nr.: 11400/0203.1.2 Fires (1396): Report nr.: 103-12- AUPE
8. Notified body (ETA)	N/A

9. Declared performance Harmonised technical specification EN 13859-1:2010, EN 13859-2:2010

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Length	EN 1848-2	m	50
Width	EN 1848-2	m	1,50 (+1,0 / -0,4 %)
Mass per unit area	EN 1849-2	g/m <sup>2</sup>	230 ± 10
Resistance to water penetration	EN 1928 Method A		W1
Water vapour transmission	EN 1931, DIN EN ISO 12572	m	Sd = 0,02 (+0,07/-0,01)
Reaction to fire	EN 13501-1	Class	E
Tensile strength MD	EN 12311-1	N/50 mm	680 ± 20
Tensile strength CD	EN 12311-1	N/50 mm	600 ± 20
Elongation MD	EN 12311-1	%	55 ± 15
Elongation CD	EN 12311-1	%	70 ± 15
Tear resistance MD	EN 12310-1	N	300 ± 15
Tear resistance CD	EN 12310-1	N	340 ± 20
After artificial ageing	EN 13859-1; EN13859-2		
Resistance to water penetration	EN 1928 method A		W 1
Tensile strength MD	EN 12311-1	N/50 mm	620 ± 20
Tensile strength CD	EN 12311-1	N/50 mm	550 ± 20
Elongation MD	EN 12311-1	%	50 ± 15
Elongation CD	EN 12311-1	%	70 ± 15
Temperature resistance		°C	-40 to +100



# RooFoil 230 MH

Declaration of Performance acc. to EU 305/2011


The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Brabrand, 03-07-2015

Supplier quality engineer, Jan Møller Thuesen

A handwritten signature in blue ink, appearing to be 'JMT', is written over a horizontal dashed line. The signature is stylized and somewhat abstract.