

DAFA Multi Sealing™

DAFA Multi Sealing is a part of DAFA AirStop System and is an elastic butyl sealing strip for special seals.



Warranty.

DAFA offers a function and product warranty for 10 years on all products associated with DAFA AirStop System.

Product

DAFA Multi Sealing is an extruded special butyl sealing strip, coated with stretch film.

Areas of application

- Constructions
- Special seals in renovation work
- Roof renovation
- Metal structures, containers, cold stores

Installation method

Remove the cover sheet. Press DAFA Multi Sealing firmly against the item.

Installation temperature:
+5 to +25 °C.

Important

Surfaces must be completely clean, dry and free of grease and dust.

Technical specifications

Basis weight	1,40 g/cm ²
Thickness	1,5 mm
Temperature resistance	-40 °C til +60 °C
Water absorption	Negligible
Resistance to UV light	Excellent
Basic raw material	Butyl rubber
Color	Black
Type	Plastic
Adhesion	Good on PE foil, metal glass, wood and concrete
Aging resistance	Good

Roll width	Length per roll	Contents per box	DAFA nr	EAN no
50 mm	5 m	8 rl.	620015438	5705636351131



Benefits

- Adheres tightly to most building materials
- Solvent-free
- Does not dry out, retains elasticity
- Does not rub off on fingers or mounting surfaces
- Very long-lasting durability
- The product does not contain harmful substances
- DAFA Multi Sealing is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings

