



# ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

DAFA Zero Waste Universal Tape DAFA A/S



# EPD HUB, HUB-0729

Publishing date 28 September 2023, last updated on 28 September 2023, valid until 28 March 2025.



Created with One Click LCA







# **GENERAL INFORMATION**

## **MANUFACTURER**

Manufacturer VP-001	DAFA A/S
Address VP-002	Holmstrupgårdvej 12, 8220 Brabrand, Denmark
Contact details VP-	dbs@dafa-group.com
Website	https://dafa-build.com/en

## **EPD STANDARDS, SCOPE AND VERIFICATION**

EI D OTANDAND	5, 0001 E AND VERNITOATION							
Program operator	EPD Hub, hub@epdhub.com							
Reference standard	EN 15804+A2:2019, ISO 14025 and ISO 21930							
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022							
Sector	Construction product							
Category of EPD	Design phase EPD							
Scope of the EPD	Cradle to gate and module C1-C4, D							
EPD author VP- 004	Mathias Walther							
EPD verification	Independent verification of this EPD and data, according to ISO 14025:  ☐ Internal certification ☐ External verification							
EPD verifier VP- 055	Magaly González Vázquez, as an authorized verifier acting for EPD Hub Limited							

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction

products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

## **PRODUCT**

Product name VP-007	DAFA Zero Waste Universal Tape
Place of production VP-008	Denmark, Aarhus
Period for data VP-013	01/02/2023-01/07/2023
Averaging in EPD VP-024-C	No averaging
Variation in GWP-fossil for A1-A3 VP-025-C	N.A.

## **ENVIRONMENTAL DATA SUMMARY**

Declared unit	1 m2
Declared unit mass	0.25467 kg
GWP-fossil, A1-A3 (kgCO2e)	7,38E-1
GWP-total, A1-A3 (kgCO2e)	6,31E-1
Secondary material, inputs (%)	3,24
Secondary material, outputs (%)	131.0
Total energy use, A1-A3 (kWh)	2,92
Total water use, A1-A3 (m3e)	1,79E-2







# PRODUCT AND MANUFACTURER

#### ABOUT THE MANUFACTURER

DAFA Building Solutions for the building industry with a focus on holistic and environmentally beneficial solutions. Products and systems that seal and make buildings long-lasting - both for renewal and new constructions.

## **PRODUCT DESCRIPTION VP-009**

The new universal tape with no liner matches all DAFA's renowned sealing systems for vapor barrier, roof, and facade foils and is ideal for other sealing tasks.

Since the tape has no liner, this saves time during installation, as no backing liner has to be removed. Time is also held on gathering waste at the construction site. The entire installation will thus be significantly faster.

Further information can be found at https://dafa-build.com/en.

## PRODUCT RAW MATERIAL MAIN COMPOSITION VP-010

Raw material category	Amount, mass- %	Material origin
Metals	0	-
Minerals	0	-
Fossil materials	100	EU
Bio-based materials	0	-

#### **BIOGENIC CARBON CONTENT VP-028-C**

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg	0.000336
Biogenic carbon content in packaging, kg C	0.029181

#### **FUNCTIONAL UNIT AND SERVICE LIFE**

Declared unit VP-011	1 m2
Mass per declared unit VP-012	0,25467 kg

#### SUBSTANCES, REACH - VERY HIGH CONCERN VP-027-C

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).







# PRODUCT LIFE-CYCLE

#### SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

	rodu stage			embl tage									S	Beyond the system boundaries				
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4		D	
х	х	х	MN D	MN D	MN D	MN D	MN D	MN D	MN D	MN D	MN D	х	х	х	х	Х		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./dem	Transport	Waste	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR.

# MANUFACTURING AND PACKAGING (A1-A3) VP-018

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

#### Manufacturing:

The manufacturing is located in Aarhus, Denmark. The tape consists of a LDPE carrier, PET scrim, and adhesive. The carrier, scrim, and adhesive are laminated together, subsequently a DAFA logo is printed on the product, and it is cut in size.

The distance to the manufacturing site is 1010 km for the different materials and is by lorry. There is no internal transport or production losses.

#### Packaging:

The tape is wrapped on a cardboard winding tube. The rolls are then packed in their dedicated cardboard boxes and placed on reusable pallet, which are also packed in PE plastic film. All packaging materials are recyclable or even reusable (pallets).

# TRANSPORT AND INSTALLATION (A4-A5)

This EPD does not cover the Transport and Installation phase.


# PRODUCT USE AND MAINTENANCE (B1-B7) VP-043-C

This EPD does not cover the use phase.

Air, soil, and water impacts during the use phase have not been studied.

## PRODUCT END OF LIFE (C1-C4, D) VP-049-C


For C1 it has been assumed that the product can be uninstalled manually by using hand-cutting tools. The end-of-life waste scenario per input material has been chosen and for each raw material, 100% incineration has been modeled under the consideration of suitable loads and benefits. The transportation distance to treatment is assumed to be 50 km and the transportation method is assumed to be lorry (C2). Module C3 accounts for energy and resource inputs for sorting and treating these waste streams for recycling and incineration with energy recovery with efficiency greater than 60%. The energy recovered mitigates 85% of district heat, and 15% of electricity. Additionally, waste that is incinerated without energy recovery or landfilled is included in Module C4. Due to the material and energy recovery potential of parts in the end-of-life product and packaging, the energy recovered from incineration replaces electricity and heat production (D). The benefits and loads of incineration are included in Module D. All end-of-life product is assumed to be sent to the closest facilities.







# MANUFACTURING PROCESS VP-019







# LIFE-CYCLE ASSESSMENT

#### **CUT-OFF CRITERIA VP-020**

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

# ALLOCATION, ESTIMATES AND ASSUMPTIONS VP-050-C

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Allocated by mass or volume
Ancillary materials	Not applicable
Manufacturing energy and waste	Allocated by mass or volume

## **AVERAGES AND VARIABILITY VP-026-C**

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	N.A.

This EPD is product and factory specific and does not contain average calculations.

#### LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent 3.8 and One Click LCA databases were used as sources of environmental data.







# **ENVIRONMENTAL IMPACT DATA**

# CORE ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF VP-029-C

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
GWP – total <sup>1)</sup>	kg CO2e	6,33E-01	5,50E-02	-5,74E-02	6,31E-01	MND	0,00E+00	2,72E-03	7,16E-01	0,00E+00	-5,08E-01								
GWP – fossil	kg CO₂e	6,34E-01	5,50E-02	4,94E-02	7,38E-01	MND	0,00E+00	2,72E-03	6,08E-01	0,00E+00	-5,08E-01								
GWP – biogenic	kg CO₂e	-1,23E-03	0,00E+00	-1,07E-01	-1,08E-01	MND	0,00E+00	0,00E+00	1,08E-01	0,00E+00	0,00E+00								
GWP – LULUC	kg CO₂e	5,58E-04	2,20E-05	2,97E-04	8,77E-04	MND	0,00E+00	1,09E-06	6,20E-06	0,00E+00	-5,86E-05								
Ozone depletion pot.	kg CFC <sub>-11</sub> e	9,34E-08	1,27E-08	5,43E-09	1,12E-07	MND	0,00E+00	6,31E-10	1,40E-09	0,00E+00	-2,67E-08								
Acidification potential	mol H <sup>+</sup> e	7,35E-03	1,56E-04	2,54E-04	7,76E-03	MND	0,00E+00	7,73E-06	1,51E-04	0,00E+00	-3,99E-03								
EP-freshwater <sup>2)</sup>	kg Pe	2,75E-05	3,92E-07	3,74E-06	3,16E-05	MND	0,00E+00	1,94E-08	1,96E-07	0,00E+00	-3,04E-05								
EP-marine	kg Ne	5,76E-04	3,12E-05	1,17E-04	7,24E-04	MND	0,00E+00	1,54E-06	6,95E-05	0,00E+00	-5,04E-04								
EP-terrestrial	mol Ne	5,93E-03	3,46E-04	7,68E-04	7,04E-03	MND	0,00E+00	1,71E-05	7,14E-04	0,00E+00	-5,91E-03								
POCP ("smog") <sup>3)</sup>	kg NMVOCe	2,44E-03	1,33E-04	1,85E-04	2,76E-03	MND	0,00E+00	6,58E-06	1,75E-04	0,00E+00	-1,58E-03								
ADP-minerals & metals <sup>4)</sup>	kg Sbe	9,05E-06	1,99E-07	3,07E-07	9,55E-06	MND	0,00E+00	9,84E-09	7,07E-08	0,00E+00	-9,48E-07								
ADP-fossil resources	MJ	1,30E+01	8,18E-01	7,47E-01	1,46E+01	MND	0,00E+00	4,05E-02	1,25E-01	0,00E+00	-5,16E+00								
Water use <sup>5)</sup>	m³e depr.	6,22E-01	3,83E-03	3,39E-02	6,59E-01	MND	MDN	MND	0,00E+00	1,90E-04	2,68E-02	0,00E+00	-1,23E-01						

<sup>1)</sup> GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

## **USE OF NATURAL RESOURCES**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Renew. PER as energy <sup>8)</sup>	MJ	1,06E+00	1,19E-02	7,28E-01	1,80E+00	MND	0,00E+00	5,89E-04	5,25E-03	0,00E+00	-2,27E+00								
Renew. PER as material	MJ	0,00E+00	0,00E+00	9,30E-01	9,30E-01	MND	0,00E+00	0,00E+00	-9,30E-01	0,00E+00	5,50E-01								
Total use of renew. PER	MJ	1,06E+00	1,19E-02	1,66E+00	2,73E+00	MND	0,00E+00	5,89E-04	-9,24E-01	0,00E+00	-1,72E+00								
Non-re. PER as energy	MJ	7,18E+00	8,18E-01	7,12E-01	8,71E+00	MND	0,00E+00	4,05E-02	1,25E-01	0,00E+00	-5,17E+00								
Non-re. PER as material	MJ	5,83E+00	0,00E+00	3,53E-02	5,86E+00	MND	0,00E+00	0,00E+00	-5,86E+00	0,00E+00	9,30E-03								
Total use of non-re. PER	MJ	1,30E+01	8,18E-01	7,47E-01	1,46E+01	MND	0,00E+00	4,05E-02	-5,74E+00	0,00E+00	-5,16E+00								
Secondary materials	kg	8,26E-03	2,78E-04	4,16E-02	5,01E-02	MND	MDN	MND	0,00E+00	1,38E-05	1,34E-04	0,00E+00	2,88E-02						
Renew. secondary fuels	MJ	1,83E-03	3,06E-06	1,67E-02	1,86E-02	MND	0,00E+00	1,52E-07	3,65E-06	0,00E+00	-2,03E-06								







Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00		
Use of net fresh water	m³	1,69E-02	1,04E-04	9,60E-04	1,79E-02	MND	MDN	MND	0,00E+00	5,16E-06	8,92E-04	0,00E+00	-6,25E-03

<sup>8)</sup> PER = Primary energy resources.

## **END OF LIFE - WASTE**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	8,94E-02	9,31E-04	3,19E-03	9,35E-02	MND	0,00E+00	4,61E-05	1,01E-04	0,00E+00	-4,01E-02								
Non-hazardous waste	kg	2,24E+00	1,65E-02	9,44E-02	2,35E+00	MND	0,00E+00	8,19E-04	2,95E-01	0,00E+00	-1,79E+00								
Radioactive waste	kg	3,27E-05	5,63E-06	2,52E-06	4,09E-05	MND	MDN	MND	0,00E+00	2,79E-07	1,68E-08	0,00E+00	-1,65E-05						

# **END OF LIFE – OUTPUT FLOWS**

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00								
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	4,08E-02	0,00E+00	0,00E+00								
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00								
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	MDN	MND	0,00E+00	0,00E+00	7,55E+00	0,00E+00	0,00E+00						








# ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO₂e	6,14E-01	5,45E-02	5,09E-02	7,19E-01	MND	0,00E+00	2,70E-03	6,08E-01	0,00E+00	-4,98E-01								
Ozone depletion Pot.	kg CFC <sub>-11</sub> e	7,12E-08	1,01E-08	4,63E-09	8,59E-08	MND	0,00E+00	5,00E-10	1,26E-09	0,00E+00	-2,19E-08								
Acidification	kg SO₂e	6,47E-03	1,28E-04	1,82E-04	6,78E-03	MND	MDN	MND	0,00E+00	6,34E-06	1,08E-04	0,00E+00	-3,38E-03						
Eutrophication	kg PO <sub>4</sub> ³e	1,32E-03	2,76E-05	1,55E-04	1,51E-03	MND	0,00E+00	1,37E-06	8,74E-05	0,00E+00	-9,06E-04								
POCP ("smog")	kg C₂H₄e	4,33E-04	6,47E-06	1,38E-05	4,54E-04	MND	0,00E+00	3,20E-07	3,02E-06	0,00E+00	-1,46E-04								
ADP-elements	kg Sbe	8,89E-06	1,94E-07	2,67E-07	9,35E-06	MND	MDN	MND	0,00E+00	9,62E-09	5,84E-08	0,00E+00	-9,57E-07						
ADP-fossil	MJ	1,30E+01	8,18E-01	7,41E-01	1,46E+01	MND	0,00E+00	4,05E-02	1,25E-01	0,00E+00	-5,16E+00								







# **VERIFICATION STATEMENT**

#### **VERIFICATION PROCESS FOR THIS EPD**

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

#### THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Magaly González Vázquez, as an authorized verifier acting for EPD Hub Limited 28.09.2023



