

DAFA Butyl 200 joint sealant

DAFA Butyl 200 is a non-hardening joint sealant used for sealing in various constructions.

Description

Butyl 200 is a non-hardening joint sealant used for sealing in a range of structures.

Application

For sealing purposes on a wide range of structures, where the butyl is applied in a "tight fit joint". This means areas where there is a form of mechanical fixing (e.g. between a concrete floor and a floor still). Used for instance in overlapping joints in moulding for caravans and for sealing joints in roof structures.

Advantage

DAFA Butyl 200 is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.

Properties

- Color: light grey
- Good UV-resistance
- Good resistance against acids and alkalis.
- The surface must be kept clean, dry and free of oil and grease.
- Can be stored for up to one year (in a dry, cool and frost-free environment)

Please contact our customers service department for further information on +45 87 47 66 66



Type/contents	Contents per box	DAFA item no	EAN no
Tube, 310 ml.	25 tubes	233400100	5705636098944
Pose 600 ml.	11 bags	620010694	5705636313764

Technical specifications

Material	Non-hardening butyl joint sealant
Temperature resistance	-40 °C to + 80 °C
Installation temperature	+5 °C to +30 °C
Storage	1 year. Store in a dry, cool and frost-free environment
Density	1,6g/cm ³
Resistance	Good UV-resistance. Good resistance against acids and alkalis
Color	Light grey

